

150T Preservation / Fine Line Vinyl

DESCRIPTION

Light blue 7-mil plasticized polyvinyl chloride film coated with an aggressive non-thermosetting rubber-resin adhesive with good ageing characteristics. Excellent for indoor or outdoor use as a surface protection and masking tape. Lifts easily from surfaces as varied as drywall and glass even after prolonged periods.

FEATURES

- UV resistant.
- Moisture and chemical resistant.
- Highly conformable.
- Leaves no residue.
- Non-tear removability.
- To prevent creepage, tape should be relaxed before applying.

PHYSICAL PROPERTIES

Carrier	Polyvinyl Chloride Film.
Adhesive	Rubber Resin
Color	Light Blue
Total Thickness	7 mil
Tensile Strength	19 lbs./in. width
Elongation	170%
Adhesion to Steel	17 oz./in. width
UV Resistance	Excellent / Residue Free
Abrasion Resistance	Excellent
Conformability	Excellent
Chemical Resistance	Excellent
Corrosion Resistance	Excellent / copper, aluminum, steel & brass
Application Temperature	40° to 120°F
Operating Temperature	-20° to 200°F
Test Method	ASTM
Shelf Life	12 months at 35% R.H. and 73°F

Physical characteristics shown are averages from tests recommended by our own procedures. A particular roll may vary slightly from these averages. The buyer should determine the suitability for his own use.