



Product Data Sheet

#398 Professional Grade Duct Tape

DESCRIPTION

High quality, tight weave polyethylene coated cloth duct tape. Confirms well to irregular surfaces. Suitable for higher demand applications – bundling, patching, HVAC, MRO requirements to name a few.

FEATURES

- Strong tape that conforms well to irregular surfaces.
- Adheres to a wide variety of surfaces.
- Tears straight, hangs straight, curl resistant.
- Outstanding performance over a wide range of temperatures.
- Complies with UL 723.
- Contributes toward satisfying EQ Credit 4.1 (Low Emitting Materials Adhesives & Sealants) under LEED®. VOC Content: <1 g/L.

APPLICATIONS

- Duct Sealing – heating, air conditioning, ventilating and refrigeration applications, sealing of seams and joints on metal air handling systems.
- Bonding, protecting, holding, repairing and patching.
- Asbestos removal and polyethylene hanging.
- MRO – Maintenance & Repair

PHYSICAL PROPERTIES

Thickness	11 mils
Tensile strength	26 lbs/in width
Adhesion to steel	80 oz/in width
Flame Spread	10
Smoke Developed	10
Maximum Temperature	200°F

The physical and performance characteristics shown are averages obtained from tests recommended by ASTM, government agencies or our own procedures. A particular roll may vary slightly from these averages and it is recommended that the purchaser determine the suitability for his own purpose.