



PRODUCT DATA SHEET

695

Double-Coated Clear Polyester Tape w/ Red PP Liner

DESCRIPTION:

695 is a CLEAR Polyester film coated on both sides with a high performance, modified Acrylic Adhesive. This product comes with a **dimensionally stable siliconized RED polypropylene release liner** making it preferred for precision die-cut applications. The adhesive system of this double-coated tape is extremely aggressive, exhibits high shear strength, and will bond well to nearly all materials; even to difficult surfaces like foams, PE and PP films. It has excellent temperature, UV, aging, water vapor, and chemical resistance. Also has good plasticizer resistance.

APPLICATIONS:

- Used for interior or exterior bonding of dissimilar materials where high shear performance is required. Used in sign making, fixing decorative moldings, print finishing and stereo mounting.
- Used for bonding rubber, plastic, metal and wood substrates; for permanent mounting of nameplates and decorative trim on appliances and furniture.
- Used in die cut applications where precise size retention is critical.

PHYSICAL PROPERTIES:

Backing	Clear Polyester film
Adhesive	Modified Acrylic Adhesive
Liner	Red siliconized PP Film
Total Thickness	6.5 mil (exclusive of liner)
Adhesion to SST	90 oz/inch
Shear Resistance	Excellent – Static & Dynamic
Temperature Resistance	up to 200°F long term

NOTE: The physical properties listed above are typical test results obtained from a series of laboratory tests and should not be used for the purpose of writing specifications. Before using this product, user shall determine the suitability of the product for his/her use; and user assumes all risks and liabilities in connection therewith. All test procedures used are in accordance with ASTM and PSTC methods.