



Provides a long-term weather-tight seal to prevent moisture, air and vapor penetration for window and door installations. Additional applications include under tile on the ridge and hip lines of roofs to prevent moisture from entering the building, deck-to-wall joints, corner board abutments, sidewall sheathing seams and any above grade critical areas that need protection against water and air leaks.

Backing:	Woven Polyethylene

Adhesive: Butyl Rubber

**Liner:** Kraft Paper Liner

Colors: Black (w/white print)

**Specs:** AAMA-711-13

**ASTM E2112** 

Fe	Features Benefits	
•	Woven Polyethylene Backing	<ul> <li>Conformable and durable</li> <li>Excellent air and moisture barrier properties</li> <li>Suitable for up to 3 years outdoor UV exposure</li> </ul>
•	Butyl Rubber Adhesive	<ul> <li>Provides permanent weather-tight seal</li> <li>Good all-temperature performance</li> <li>Compatible with sealants and caulking</li> <li>Self-healing after puncture</li> <li>Used properly, can contribute toward requirements for EA Credit 1 (Optimize Energy Performance) under LEED®</li> </ul>
•	Paper Release Liner	Easy to remove

Product ID	Size	Units / Case
51862740	4" (96mm) x 100 ft	6 - Cello Wrapped
51862760	6" (144mm) x 100 ft	6 - Cello Wrapped

Electro Tape

**CONTACT A REPRESENTATIVE TODAY!** 

**(800) 999-2218** 

Explore Our Catalog! Visit electrotape.com



REQUEST A CATALOG TODAY!

OR VISIT OUR ONLINE VIRTUAL CATALOG